

## Product Sheet

# LED HARDWAX OIL

Our revolutionary LED Hardwax Oil is a VOC-free, penetrative coating containing a unique mix of oils, waxes, resins and additives. Our curing technology means that the coating cures and hardens instantaneously under LED light. When finished, surfaces are immediately resilient and protected against dirt and moisture.



### CHARACTERISTICS

instant  
dry

- Instantly dry upon LED light exposure
- 100% VOC free
- Dirt and moisture repellent, highly resistant to chemicals.
- Provides deep colouring of the wood surface as well as on previously applied stains.
- Finished products can be packaged immediately at the end of the production line.

### DIRECTION FOR USE

#### SURFACE PREPARATION

Sand surface with 120 grit sandpaper. This enables the best penetration of Hardwax Oil.

#### INSTRUCTIONS

1. Apply LED Hardwax Oil using a roller, buffing pad, or brush.
2. Rag off any excess oil.
3. Cure the coating by exposing it to LED light.
4. Additional coats can be applied immediately upon curing.
5. Sand in between coats to achieve desired hand feel.

#### COVERAGE:

By Machine - 70-80sqm/L\*

By Hand - 40-50sqm/L\*

\*Indicative coverage only

The ideal distance between the wood surface and LED unit is 2.5 cm.

#### STORAGE

Store in a dry, frost-free and enclosed area.

Always close the opened packing to prevent pre-curing.

# APPLICATIONS

LED Hardwax Oil can be applied to all wood types, stained wood, concrete and stone.



Timber Flooring



Internal Linings



Concrete



Furniture